

# Post T

## VERSION CORTEN



accessories for vineyards and orchards

Via Gitti, 56 - 25060 Marcheno (BS) Italia tel. +39 030 861272

fax +39 030 8966654 e-mail [info@vineyardstore.net](mailto:info@vineyardstore.net) [www.vineyardstore.net](http://www.vineyardstore.net)



VINEYARDSTORE

### 1. PRODUCT NAME AND DESCRIPTION

Pole fence

Section "T" progressive modular lengths.

Anime bearing holes  $\varnothing$  9 mm spacers opportunely, to support wire tension

And support for the network and for securing the arrows contrast.

### 2. MATERIAL - MECHANICAL

CORTEN: S 275 J R W W

or

CORTEN: S 355 J R W W

### 3. FINISH

#### a. Lamination (layer thickness of approximately 80 microns)

Full course of treatment consists of:

Sandblasting (Sa 2 1/2) with metal grit, applications of powder coating based on polyester pure, curing in an oven at 200 ° C.

On request, the application of paint may be preceded by: deglassaggio hot, hot phosphating with zinc salts and drying.

#### b. Galvanizing (UNI 5742-66 Second Deposit 450/500 g/m<sup>2</sup>)

Full course of treatment consists of:

Sandblasting (Sa 2 1/2) with metal grit, pickling, fluxing, preheating, hot dip galvanizing by immersion in a bath of zinc-purity (99.995%) melted.

### 4. CHARACTERISTICS GEOMETRIC STATISTICS:

SECTION TYPE	DIMENSION Mm	THEORETICAL WEIGHT Kg/m	Jx Cm <sup>4</sup>	Wx Cm <sup>3</sup>
T	40x40x4,5	2,70	5,056	1,786
T	40x40x5	3,10	5,560	1,972
T	50x50x6	4,45	13,116	3,715
T	60x60x7	6,60	26,586	6,270