
Galvanized Stakes


TECHNICAL SPECIFICATIONS



Length: 2.50m - 2.75m

Gauge: 1.5mm

Cross section:





accessories for vineyards and orchards

Via Gitti, 56 - 25060 Marcheno (BS) Italia tel. +39 030 861272

fax +39 030 8966654 e-mail info@vineyardstore.net www.vineyardstore.net

The brace as well as being the fundamental support of the screw to the proper development of the vertical toward the wire quay has also in the first stages of farming importance for the resistance which must offer to the machines for the processing of of the sub-row.

The greater the mechanical strength of the guardian, the greater the protection offered to the screw bumps. For this purpose were made with steel rods pregalvanized coating lightweight (275 g / m ^ 2).

The tutors sheet have small ribs on the surface which result in an increase of thickness (the thickness of the material increases up to 2 times its initial thickness).

This is due to a deformation process known as work hardening which increases the strength of the material.

The particular shape of our tutors and ribbed galvanized sheet allows you to have:

- Increased load capacity
- Improved grip
- Higher voltage
- 30% less deformation
- Less weight (very light to carry)
- No rust

NAME	ТҮРЕ	SECTION	AVAILABLE LENGHT	FINISHING	THICKNESS
GALVANIZED STAKES	Stakes	6 mm diam	1,20 meters	Post-galvanized 25 Micron	1,5 mm